

IdP Login Form Customization

Templates and Customization



SWITCH

SWITCHaai Team
aai@switch.ch

 © SWITCH 2015

Overview

- How to
 - Customize look and feel
 - Customize messages/languages
 - Add text to your login site

 © SWITCH 2015


Web Login Service - Mozilla Firefox

Web Login Service

https://aai-login.example.org/idp/profile/SAML2/Redirect/SSO;jsessionid=...

Most Visited Training Page AAI Demo IdP Installation Guide IdP Status

Cookies CSS Information Miscellaneous Outline Tools View Source Options Developer

SWITCHaai 

Forgot your password? Need Help?

Username

Password

Clear prior granting of permission for release of your information to this service.

You are about to access the service:
AAI Demo Resource
 Description as provided by this service:
It illustrates the basic principles of AAI with various examples of Shibboleth features.

Web Login Service - Mozilla Firefox

Web Login Service

https://aai-login.example.org/idp/profile/SAML2/Redirect/SSO;jsessionid=...

Most Visited Training Page AAI Demo IdP Installation Guide IdP Status

Cookies CSS Information Miscellaneous Outline Tools View Source Options Developer

SWITCHaai

Forgot your password? Need Help?

Username

Password

Clear prior granting of permission for release of your information to this service.

You are about to access the service:
AAI Demo Resource
 Description as provided by this service:
It illustrates the basic principles of AAI with various examples of Shibboleth features.

- Toggle Tools Ctrl+Shift+I
- Inspector Ctrl+Shift+C
- Web Console Ctrl+Shift+K
- Debugger Ctrl+Shift+S
- Style Editor Shift+F7
- Performance Shift+F5
- Network Ctrl+Shift+Q
- Developer Toolbar Shift+F2
- WebIDE Shift+F8
- Browser Console Ctrl+Shift+J
- Responsive Design View Ctrl+Shift+M
- Eyedropper
- Scratchpad Shift+F4
- Page Source Ctrl+U
- Get More Tools
- Work Offline

Web Login Service - Mozilla Firefox

Web Login Service

https://aai-login.example.org/idp/profile/SAML2/Redirect/SSO;jsessionior

Most Visited Training Page AAI Demo IdP Installation Guide IdP Status

Cookies CSS Information Miscellaneous Outline Tools View Source Options Developer

SWITCHaai

Forgot your password? Need Help?

Username
student1

Password

Clear prior granting of permission for release of your information to this service.

Login

You are about to access the service:
AAI Demo Resource

Description as provided by this service:
It illustrates the basic principles of AAI with various examples of Shibboleth features.

Layout

- Change the look and feel in
/opt/shibboleth-idp/edit-webapp
(images and css)
- Place additional web resources in the edit-webapp directory, not the webapp directory. The webapp directory is replaced upon every IdP upgrade.
- Rebuild the idp.war file and restart tomcat

Spring message properties

- in `/opt/shibboleth-idp/messages` you find
 - `authn-messages.properties`
 - `error-messages.properties`
 - `consent-messages.properties`these messages are used in the velocity template
- internationalization:
 - `consent-messages_de.properties`
 - `consent-messages_fr.properties` etc.

error-messages.properties

in `/opt/shibboleth-idp/messages/error-messages.properties`

General strings

`idp.title = Web Login Service`

`idp.title.suffix = Error`

`idp.logo = /images/example.org.png`

`idp.logo.alt-text = Example Home Organisation`

`idp.logo.target.url = http://www.example.org`

`idp.message = An unidentified error occurred.`

`idp.footer = Insert your footer text here.`

Error key to title and message mappings

`unexpected.title = Unexpected Error`

`unexpected.message = An unexpected error was encountered, usually reflecting a configuration or software error.`

authn-messages.properties

in /opt/shibboleth-idp/messages/authn-messages.properties

```
idp.login.loginTo = Login to
idp.login.username = Username
idp.login.password = Password
idp.login.donotcache = Don't Remember Login
idp.login.login = Login
idp.login.forgotPassword = Forgot your password?
idp.login.forgotPassword.url = https://support.example.org
idp.login.needHelp = Need Help?
```

authn-messages.properties

in /opt/shibboleth-idp/messages/authn-messages.properties

```
# Classified Login Error messages
UnknownUsername = bad-username
InvalidPassword = bad-password
ExpiredPassword = expired-password
AccountLocked = account-locked
bad-username.message = The username you entered cannot be identified.
bad-password.message = The password you entered was incorrect.
expired-password.message = Your password has expired.
account-locked.message = Your account is locked.
```

Velocity Properties

```
<a class="aai" href="#"
#springMessage("idp.login.forgotPassword.url")
">
#springMessageText("idp.login.forgotPassword",
"Forgot your password?")
</a>
```

SWITCHaai 

[Forgot your password?](#) [Need Help?](#)

Username

Password

Clear prior granting of permission for release of your information to this service.

Technical support:
E-Mail: [Helpdesk](#)
Phone (internal): 9
Phone (external): +41
IT Services: [IT Services Webpage](#)

You are about to access the service:
AAI Demo Resource

Description as provided by this service:
It illustrates the basic principles of AAI with various examples of Shibboleth features.

Velocity

- The Apache Velocity Engine is a free open-source templating engine.
- clean separation between the presentation tier and business tiers
- VTL (Velocity Template Language)
 - References begin with \$
 - Directives begin with #
 - A single line comment begins with ## and finishes at the end of the line.
 - Multi-line comments, which begin with #* and end with *#

Login and intercept

- The velocity templates are under `/opt/shibboleth-idp/views`
 - `login.vm`
 - `login-error.vm`
 - `intercept/attribute-release.vm`
 - `intercept/terms-of-use.vm`
 - `error.vm`are most used (no restart required)
- Additional custom pages can be added , e.g. for expiring passwords, locked accounts etc.

Some Velocity Properties

- `$rpUIContext.informationURL`
- `$rpUIContext.logo`
- `$rpUIContext.organizationDisplayName`
- `$rpUIContext.organizationName`
- `$rpUIContext.organizationURL`
- `$rpUIContext.privacyStatementURL`
- `$rpUIContext.serviceDescription`
- `$rpUIContext.serviceName`

Velocity Properties

```
#set ($name = $rpUIContext.serviceName)
#if ($name)
  <div class="space">
    <em>$encoder.encodeForHTML($name)</em>
  </div>
#end
```


Hands On I - III

- change the background-color of the class `.aai_login_field` from grey to any other color
- return the following error message on the login form in case of invalid username or incorrect password:

“ The credentials you entered are incorrect.”
- Start to adapt the `login.vm` in such way that it looks like your production IdP.

Example Solution I

- change the background-color in `aai_login_field` class in `/opt/shibboleth-idp/edit-webapp/css/main.css`

```
.aai_login_field { ...  
    background-color: #4EEE94;  
    ... }
```
- rebuild and restart tomcat

```
sudo JAVACMD=/usr/bin/java /opt/shibboleth-idp/bin/  
build.sh -Didp.target.dir=/opt/shibboleth-idp  
sudo /etc/init.d/tomcat7 restart
```
- might be you need to reload linked stylesheets in the browser to see the effect

Example Solution II

- Edit authn-messages.properties

```
UnknownUsername = bad-credentials  
InvalidPassword = bad-credentials  
bad-credentials.message = The credentials  
you entered are incorrect.
```